

SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: SILKOLENE PRO CCA ULTRA

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Anticorrosion product

Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier FUCHS LUBRICANTS (UK) PLC.
New Century Street
Hanley
Stoke-on-Trent, Staffordshire, ST1 5HU
UK

Telephone: +44 (0) 1782 203700

Contact Person: Product Safety department
Telephone: +44 (0) 1782 203700
E-mail: product.safety@fuchs-oil.com

1.4 Emergency telephone number: UK NHS: Dial 111. Ireland NPIS: Dial +353 1 8092566.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to regulation (EU) 1272/2008 (CLP).

Classification according to Regulation (EC) No 1272/2008 as amended.

Health Hazards

Skin irritation	Category 2	H315: Causes skin irritation.
Serious eye damage	Category 1	H318: Causes serious eye damage.
Specific Target Organ Toxicity - Repeated Exposure	Category 2	H373: May cause damage to organs through prolonged or repeated exposure.

Hazard summary

Physical Hazards: No data available.

2.2 Label Elements

Contains: Phosphate ester derivative
DEA

Product name: SILKOLENE PRO CCA ULTRA



Signal Words: Danger

Hazard Statement(s): H315: Causes skin irritation.
H318: Causes serious eye damage.
H373: May cause damage to organs through prolonged or repeated exposure.

Precautionary Statement

Prevention: P260: Do not breathe dust/fume/gas/mist/vapors/spray.
P262: Do not get in eyes, on skin, or on clothing.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response: P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310: Immediately call a POISON CENTER/doctor.

2.3 Other hazards: By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

General information: Mixture based on emulsified waxes and anticorrosion additives. This product is applied only as solution or emulsion in water.

Chemical name	Identifier	Concentration *	REACH Registration No.	Notes
acid, ionic equilibrium with organic bases	Neutralisation product (*)	10,00 - <25,00%		
Phosphate ester derivative	EC: 609-691-9	10,00 - <20,00%		
sec. alkanolamine, ionic equilibrium with acids	Neutralisation product (*)	10,00 - <20,00%		
DEA	EINECS: 203-868-0	5,00 - <10,00%	01-2119488930-28	
Boric acid	EINECS: 233-139-2	0,10 - <5,50%	01-2119486683-25	**
tert. alkanolamine, ionic equilibrium with acids	Neutralisation product (*)	5,00 - <10,00%		

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

** Regulation (EC) No. 1907/2006, REACH Article 59(1). Candidate List

(*) Neutralisation product: Equilibrium of Ionic Pairs in aqueous solution according to REACH Annex V, 4.

Product name: SILKOLENE PRO CCA ULTRA

Classification

Chemical name	Identifier	Classification
acid, ionic equilibrium with organic bases	Neutralisation product (*)	CLP: Acute Tox. 4;H302, Eye Irrit. 2;H319, Skin Irrit. 2;H315
Phosphate ester derivative	EC: 609-691-9	CLP: Skin Irrit. 2;H315, Eye Dam. 1;H318
sec. alkanolamine, ionic equilibrium with acids	Neutralisation product (*)	CLP: Acute Tox. 4;H302, Eye Irrit. 2;H319, STOT RE 2;H373, Aquatic Chronic 3;H412
DEA	EINECS: 203-868-0	CLP: Acute Tox. 4;H302, STOT RE 2;H373, Skin Irrit. 2;H315, Eye Dam. 1;H318, Aquatic Chronic 3;H412
Boric acid	EINECS: 233-139-2	CLP: Repr. 1B;H360Df
tert. alkanolamine, ionic equilibrium with acids	Neutralisation product (*)	CLP: Acute Tox. 4;H302, Acute Tox. 3;H311, Acute Tox. 3;H331, Flam. Liq. 3;H226, Eye Irrit. 2;H319, Skin Irrit. 2;H315

CLP: Regulation No. 1272/2008.

For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Skin Contact: Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.

Ingestion: Rinse mouth. Call a POISON CENTER/doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed: Risk of serious damage to eyes. Causes skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: CO₂, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

Unsuitable extinguishing media: Water with a full water jet.

Product name: SILKOLENE PRO CCA ULTRA

5.2 Special hazards arising from the substance or mixture:	During fire, gases hazardous to health may be formed.
5.3 Advice for firefighters	
Special fire fighting procedures:	Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.
Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:	Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away. In case of spills, beware of slippery floors and surfaces.
6.2 Environmental Precautions:	Prevent from spreading (e.g. by binding or oil barriers). Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.
6.3 Methods and material for containment and cleaning up:	Absorb with liquid-binding material (sand, diatomite, acidbinders, universal binders, sawdust). Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.
6.4 Reference to other sections:	See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.
	Dike for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:	Avoid contact with skin. Wash hands thoroughly after handling. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Prevent formation of aerosols. Observe good industrial hygiene practices. Provide adequate ventilation.
7.2 Conditions for safe storage, including any incompatibilities:	Local regulations concerning handling and storage of waterpolluting products have to be followed.
7.3 Specific end use(s):	not applicable
Storage Class:	10-13, combustible / non-combustible liquids and solids

Product name: SILKOLENE PRO CCA ULTRA

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

None of the components have assigned exposure limits.

8.2 Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information:

Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.

Eye/face protection:

Safety glasses (EN 166) recommended during refilling. Avoid contact with eyes. Wear closed protection glasses.

Skin protection

Hand Protection:

Material: Nitrile butyl rubber (NBR).
Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Other:

Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.

Respiratory Protection:

Ensure good ventilation/exhaustion at the workplace. Avoid breathing vapour/ aerosol.

Thermal hazards:

Not known.

Hygiene measures:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

Environmental Controls:

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:

liquid

Product name: SILKOLENE PRO CCA ULTRA

Form:	liquid
Color:	Pale yellow
Odor:	Characteristic
Odor Threshold:	Not applicable for mixtures
pH:	8,3 (30 g/l)
Freezing point:	Not applicable for mixtures
Boiling Point:	not applicable
Flash Point:	not applicable
Evaporation Rate:	Not applicable for mixtures
Flammability (solid, gas):	Value not relevant for classification
Flammability Limit - Upper (%)-:	Not applicable for mixtures
Flammability Limit - Lower (%)-:	Not applicable for mixtures
Vapor pressure:	Not applicable for mixtures
Vapor density (air=1):	Not applicable for mixtures
Density:	1,10 g/ml (15,00 °C)
Solubility(ies)	
Solubility in Water:	Soluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	Not applicable for mixtures
Autoignition Temperature:	Value not relevant for classification
Decomposition Temperature:	Value not relevant for classification
Kinematic viscosity:	68 mm ² /s (40 °C)
Explosive properties:	Value not relevant for classification
Oxidizing properties:	Value not relevant for classification
9.2 Other information	No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity:	Stable under normal use conditions.
10.2 Chemical Stability:	Stable under normal use conditions.
10.3 Possibility of hazardous reactions:	Stable under normal use conditions.
10.4 Conditions to avoid:	Stable under normal use conditions.
10.5 Incompatible Materials:	Strong oxidizing substances. Strong acids. Strong bases.
10.6 Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

SECTION 11: Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
Ingestion:	No data available.

Product name: SILKOLENE PRO CCA ULTRA

Skin Contact: Causes skin irritation.

Eye contact: Causes serious eye damage.

11.1 Information on toxicological effects

Acute toxicity

Oral

Product:	ATEmix: 2.567 mg/kg
Specified substance(s) acid, ionic equilibrium with organic bases	LD 50 (Rat): 1.100 mg/kg
Phosphate ester derivative	LD 50 (Rat): > 2.001 mg/kg
sec. alkanolamine, ionic equilibrium with acids	LD 50 (Rat): 1.600 mg/kg
DEA	LD 50 (Rat): 1.600 mg/kg
Boric acid	LD 50 (Rat, Male): 3.450 mg/kg (OECD 401)
tert. alkanolamine, ionic equilibrium with acids	LD 50 (Rat): 1.320 mg/kg

Dermal

Product:	ATEmix: 5.952 mg/kg
Specified substance(s) acid, ionic equilibrium with organic bases	LD 50 (Rabbit): > 2.001 mg/kg
sec. alkanolamine, ionic equilibrium with acids	LD 50 (Rabbit): 12.970 mg/kg
DEA	LD 50 (Rabbit): 12.970 mg/kg
Boric acid	LD 50 (Rabbit): > 2.001 mg/kg
tert. alkanolamine, ionic equilibrium with acids	LD 50 (Rabbit): 1.100 mg/kg

Inhalation

Product:	ATEmix: 59,52 mg/l Vapour ATEmix: 151,52 mg/l Dusts, mists and fumes
Specified substance(s) Boric acid	LC 50 (Rat, Female, Male, 4 h): > 2,12 mg/l (OECD 403)

Skin Corrosion/Irritation:

Product: Based on available data, the classification criteria are met.

Product name: SILKOLENE PRO CCA ULTRA

Serious Eye Damage/Eye Irritation:

Product: Based on available data, the classification criteria are met.

Respiratory or Skin Sensitization:

Product: Skin sensitizer: Based on available data, the classification criteria are not met.
Respiratory sensitizer: Based on available data, the classification criteria are not met.

Specified substance(s)

DEA

No sensitizing effect (guinea pig); OECD 406

Boric acid

No sensitizing effect (guinea pig); OECD 406

Germ Cell Mutagenicity

Product: Based on available data, the classification criteria are not met.

Carcinogenicity

Product: Based on available data, the classification criteria are not met.

Reproductive toxicity

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product: Based on available data, the classification criteria are met.

Aspiration Hazard

Product: Based on available data, the classification criteria are not met.

Other Adverse Effects:

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity

Product: Based on available data, the classification criteria are not met.

Fish

Specified substance(s)

acid, ionic equilibrium with organic bases LC 50 (Fish, 96 h): 122 mg/l

Phosphate ester derivative LC 50 (Fish, 96 h): > 101 mg/l

sec. alkanolamine, ionic equilibrium with acids LC 50 (Fish, 96 h): 1.460 mg/l

Product name: SILKOLENE PRO CCA ULTRA

DEA LC 50 (Fish, 96 h): 1.460 mg/l

Boric acid LC 50 (Fish, 96 h): 456 mg/l

tert. alkanolamine, ionic
equilibrium with acids LC 50 (Fish, 96 h): 147 mg/l

Aquatic Invertebrates
Specified substance(s)
acid, ionic equilibrium
with organic bases

EC 50 (Water Flea, 48 h): 68 mg/l

sec. alkanolamine, ionic
equilibrium with acids EC 50 (Water Flea, 48 h): 55 mg/l

DEA EC 50 (Water Flea, 48 h): 55 mg/l

Boric acid EC 50 (Water Flea, 48 h): 133 mg/l

tert. alkanolamine, ionic
equilibrium with acids EC 50 (Water Flea, 48 h): 165 mg/l

Chronic ToxicityProduct: Based on available data, the classification criteria are not met.

Aquatic Invertebrates
Specified substance(s)
DEA

NOEC (Water Flea, 21 d): 0,78 mg/l

Toxicity to Aquatic Plants
Specified substance(s)
acid, ionic equilibrium
with organic bases

EC 50 (Alga, 72 h): 81 mg/l

sec. alkanolamine, ionic
equilibrium with acids EC 50 (Alga, 72 h): 75 mg/l

Boric acid EC 50 (Alga, 72 h): 229 mg/l

tert. alkanolamine, ionic
equilibrium with acids EC 50 (Alga, 72 h): 44 mg/l

12.2 Persistence and Degradability

Biodegradation

Product: Not applicable for mixtures

Specified substance(s)

DEA 93 % (28 d, OECD 301F) Readily biodegradable

12.3 Bioaccumulative Potential

Product: Not applicable for mixtures

12.4 Mobility in Soil:

Product: Not applicable for mixtures

Product name: SILKOLENE PRO CCA ULTRA

12.5 Results of PBT and vPvB assessment: The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Other Adverse Effects: No data available.

Water Hazard Class (WGK): WGK 1: slightly water-endangering.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information: Dispose in accordance with all applicable regulations.

Disposal methods: Do not empty into drains; dispose of this material and its container in a safe way. When storing used products, ensure that the waste categories and mixing instructions are observed.

European Waste Codes

07 06 04*: other organic solvents, washing liquids and mother liquors

SECTION 14: Transport information

ADR/RID

14.1 UN Number: —
 14.2 UN Proper Shipping Name: —
 14.3 Transport Hazard Class(es)
 Class: Non-dangerous goods
 Label(s): —
 Hazard No. (ADR): —
 Tunnel restriction code: —
 14.4 Packing Group: —
 14.5 Environmental hazards: —
 14.6 Special precautions for user: —

ADN

14.1 UN Number: —
 14.2 UN Proper Shipping Name: —
 14.3 Transport Hazard Class(es)
 Class: Non-dangerous goods
 Label(s): —
 14.3 Packing Group: —
 14.5 Environmental hazards: —
 14.6 Special precautions for user: —

Product name: SILKOLENE PRO CCA ULTRA

IMDG

- 14.1 UN Number: –
- 14.2 UN Proper Shipping Name: –
- 14.3 Transport Hazard Class(es)
 - Class: Non-dangerous goods
 - Label(s): –
 - EmS No.: –
- 14.3 Packing Group: –
- 14.5 Environmental hazards: –
- 14.6 Special precautions for user: –

IATA

- 14.1 UN Number: –
- 14.2 Proper Shipping Name: –
- 14.3 Transport Hazard Class(es):
 - Class: Non-dangerous goods
 - Label(s): –
- 14.4 Packing Group: –
- 14.5 Environmental hazards: –
- 14.6 Special precautions for user: –

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

Regulation (EC) No. 2037/2000 Substances that deplete the ozone layer: none

Regulation (EC) No. 850/2004 on persistent organic pollutants: none

National Regulations

Local regulations are to be kept

Water Hazard Class (WGK): WGK 1: slightly water-endangering.

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Revision Information: Vertical lines in the margin indicate an amendment.

Product name: SILKOLENE PRO CCA ULTRA

Wording of the H-statements in section 2 and 3

H226	Flammable liquid and vapor.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H360Df	May damage the unborn child. Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Other information: The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies. The classification results from the Conventional Method mentioned in regulation EU 1272/2008 (CLP).

Revision Date: 22.04.2016

Disclaimer: The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.